



P25383-01 (English version)

Information Processing system and Method strengthen in Password

5

BACKGROUND OF THE INVENTION**FIELD OF THE INVENTION**

The present invention relates to information processing system and a method of processing the information, and more specifically it relates to a technique of processing information to improve benefit and convenience of the operator, and to ensure security of the recorded information.

10

DESCRIPTION OF THE PRIOR ART

With the wide use of information processors in recent years, value of information themselves recorded in secondary memories are becoming far greater than value of main bodies of the information processors. Since the secondary memories are removable in general, there is a risk that the recorded information is used illegitimately by third parties who have stolen them. Thus, there are demands for security techniques that render the information in the secondary memories not readable by even the third parties who have stolen them.

15

20

Information processors and information processing systems of the prior art, when stolen, can be disassembled so as to take out secondary memories therefrom. When this happened, the information is not prevented from an illegitimate using by means of only a password used for startup if any of the removed secondary memories is connected to another information processor and used wrongfully. For this reason, in the conventional information processors, upon removing the information recorded in the secondary memories are rendered not useable even by setting different passwords (hereinafter referred to as "secondary password") for the secondary memories themselves.

25

09:21:87.080404

With the conventional information processors and the information processing systems, however, there were often cases that operators do not set passwords for startup to save a tiresome setting up operation of passwords. There were also many cases of not setting secondary passwords for the secondary memories. Then there exist great risks of information leakage for the above reason.

On the other hand, there are often cases in which an information processor is used only in a combination of the information processor and a display device, without connecting an ordinary keyboard. There are such cases with automated teller machines at shop fronts of banks, shopping information machines announcing services in shopping floors, and the like. In such cases operators take desired information and guidance by simply inputting supplementary information with such ancillary input devices as touch panels integrated to display devices without such input devices as the regular keyboards. Furthermore, there are also many such cases for automated continuous presentation of store guide and explanation of merchandises at shop fronts that do not use even the above-referred touch panels, let alone the input devices like keyboards. In any of these information processing systems, although it is necessary to set passwords beforehand to prevent an information processor and a secondary memory from leaking information stored, but it is tiresome for a worker to input a startup password and a secondary password with a keyboard, for the processing system and for the secondary memory every time before starting. This does not contribute to efficiency of the workers. However, without keyboard as means of inputting the passwords, this makes the information processor not only impossible to start, but also unable to use even necessary information stored in the secondary memory.

The present invention, therefore, is intended to avoid an annoying work for the operator to input the passwords at each time as stated above, and to minimize the risk of information leakage in case the main unit or the secondary memory of the information processor is stolen. That is, the information processor and the information processing system are started regardless of presence or absence of passwords, when an input

device capable of handling input of the passwords is not connected, even if there are the passwords set in them. On the other hand, the information processor and the information processing system are started only when the passwords are correctly input with the original input device or another input device, if there are the passwords set in
5 them. Consequently the present invention, thus, prevents the information from illegitimate using while it improves convenience of the operator.

SUMMARY OF THE INVENTION

In order to achieve the above-stated object, an information processing system of
10 the present invention comprises:

(a) a main unit of information processor;

(b) an input means detachable from the main unit of the information processor,
for setting a startup password used for starting the main unit of the information
processor;

15 (c) a startup password storage means for storing the startup password set by the input means;

(d) a startup password presence checking means for determining whether or not
the startup password is stored in the startup password storage means; and

(e) a startup password request means for requesting an operator to set a startup
20 password, wherein:

(i) the startup password request means requests setting a startup password by
the input means for starting the main unit of the information processor, if the input
means is connected to the main unit, and when a result of determination of the startup
password presence checking means indicates absence of the startup password;

25 (ii) the main unit of the information processor is turned into a starting mode,
if the input means is connected to the main unit of the information processor, and when
the result determined by the startup password presence checking means indicates
presence of the startup password; and

(iii) the main unit of the information processor is turned into a starting mode irrespective of the result determined by the startup password presence checking means as to whether presence or absence of the password, if the input means is not connected to the main unit of the information processor.

5

Furthermore, to achieve the above object in an information processing system having a main unit of information processor and an input means detachable from the main unit of the information processor, a method of processing information comprises the steps of:

10

(a) setting a startup password by the input means for starting the main unit of the information processor;

(b) storing the above-set startup password;

(c) determining presence or absence of the startup password in storage; and

(d) requesting an operator to set a startup password, whereby:

15

(i) executing the step (d), if the input means is connected to the main unit of the information processor, and when a result of determination in the step (c) indicates absence in storage;

20

(ii) turning the main unit of the information processor into a startup mode, if the input means is connected to the main unit of the information processor, and when the result of determination in the step (c) indicates presence in storage; and

(iii) turning the main unit of the information processor into a startup mode irrespective of the result of determination in the step (c), if the input means is not connected to the main unit of the information processor.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a block diagram representing an information processing system of an exemplary embodiment according to the present invention; and

Fig. 2 is a process flowchart during startup of a basic input-output system (BIOS)

of the information processing system of the exemplary embodiment according to this invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

5 An exemplary embodiment of the present invention will be described hereinafter with reference to Fig. 1 and Fig. 2. Fig. 1 is a block diagram of an information processing system of this exemplary embodiment.

10 In Fig. 1, the information processing system comprises a central processing unit (CPU) 1 for controlling the entire system, a basic input-output system (BIOS) 2 representing a program to be executed first for initialization and so on of the information processing system when a power supply in the information processing system is turned on, a detachable input device 3 defining an input means such as a keyboard for inputting a password and the like, a display device 4 for displaying a password input screen and the like, a nonvolatile memory 5 for storing the password and so on, and a secondary memory 6 such as a hard disk drive (HDD).

15 A main unit of the information processor comprises, in general, the central processing unit (CPU) 1, the basic input-output system (BIOS) 2, the nonvolatile memory 5, for storing the password and the like, and the secondary memory 6 such as a hard disk drive (HDD).

20 The display device 4, which displays the password input screen and the like, defines display means such as a CRT, a liquid crystal display, and the like. In one case, it is integrated into the main unit of the information processor, and it may be separated from the main unit of the information processor in another case. In addition, the display device 4 may include an ancillary input means such as a touch panel for
25 inputting supplementary information.

The secondary memory 6 may be comprised of any such means as a floppy disk drive (FDD), a compact disk read only memory device (CD-ROM), a compact disk recording device (CD-R), a compact disk read/write device (CD-R/W), a compact disk

09842187.080101

random access memory device (CD-RAM), a digital video disk read only memory device (DVD-ROM), a digital video disk recording device (DVD-R), a digital video disk read/write device (DVD-R/W), a digital video disk random access memory device (DVD-RAM), a digital tape recording device, or the like, besides the hard disk drive (HDD). Moreover, there may be such cases that the secondary memory 6 is integrated into the main unit of the information processor, and it is separated from the main unit of the information processor in a removable manner. Furthermore, the secondary memory 6 is normally removable even if it is integrated with the main unit of the information processor.

Fig. 2 is a process flowchart during startup of the basic input-output system (BIOS) in the present exemplary embodiment.

In Fig. 2, a power-on step 21 is for turning on the power supply of the information processing system. The information processing system then starts executing the basic input-output system (BIOS) 2. A recorded password check step 22 is for checking the nonvolatile memory 5 and the secondary memory 6 it determines whether or not the secondary password for the secondary memory 6 is stored in any of them. If the secondary password are stored in any of the nonvolatile memory 5 and the secondary memory 6, a state of the system passes on to an input means check step 24. If the startup password and the secondary password are not stored in the nonvolatile memory 5 and the secondary memory 6, the state of the system passes on to a password setting display step 23, and displays a startup password and secondary password setting screen in the display device 4 such as a CRT or a liquid crystal display representing the display means, and urges the operator to set a startup password and a secondary password. In this password setting display step 23 here, the display device 6 may be substituted by a vocal means, in place of the screen display, to produce vocal sound for urging the operator to set the startup password and the secondary password with the voice.

The input means check step 24 is for detecting whether or not an input device 3, or the input means, such as a keyboard, for example, is connected to the main unit of the information processor. The state of the system goes on to a password input request step 25, if the input device 3 is connected to the main unit of the information processor.

5 If no input device 3 is connected to the main unit of the information processor, the state of the system goes on to a password acquisition step 26, and acquires the secondary password for the secondary memory 6 stored in the nonvolatile memory 5. Then, the state of the system goes on to a password security unlock step 28. The password input request step 25 is materialized by displaying a password input setting screen in the
10 display device 4, or the display means such as a CRT, a liquid crystal display and the like, for instance. The state of the system goes on to a password matching step 27 when the operator inputs a startup password according to the password input setting screen .

Here, a vocal means may be used in place of the display means to urge the
15 operator to set the startup password with the voice.

The password matching step 27, there is checks whether or not the the secondary password input in the password input request step 25 matches with the secondary password for the secondary memory 6, stored in the nonvolatile memory 5 and the secondary memory 6. If the input secondary password is in agreement with
20 the secondary password stored in the nonvolatile memory 5 and the secondary memory 6, the state of the system goes on to the password security unlocking step 28. If the input secondary password is in discordance with those stored in the nonvolatile memory 5 and the secondary memory 6, the state of the system goes on to a startup process interrupting step 210, where the discordance interrupts starting process of the
25 entire information processing system or the main unit of the information processor.

The password security unlocking step 28 is for setting within the secondary memory 6 either the startup password which is input in the password input request step 25, or the secondary password acquired in the password step 26. Upon unlocking the

09842187-080101

security lock, the state of the system goes on to a startup process continuation step 29 to continue the starting process of the entire information processing system or the main unit of the information processor.

If the secondary memory 6 is removed, and then connected to another
5 information processor of the same model but different from the main unit of the information processor in which the secondary password is set, this another information processor checks whether or not the secondary password for this removed secondary memory 6 is stored in a nonvolatile memory 5 within the another information processor and the removed secondary memory 6. If the secondary password is stored in the
10 nonvolatile memory 5 and the secondary memory 6, the state of the system goes on to the input means check step 24. If the secondary password is not stored in the nonvolatile memory 5 of the another information processor and the secondary memory 6, the state of the system goes on to a password input setting display step 23, and displays a secondary password setting screen in a display device 4 defining display
15 means such as a CRT or a liquid crystal display, and urges the operator to set a secondary password. At this step, an illegitimate operator is able merely to input a random startup password and a random secondary password, since he/she has no knowledge of the secondary password especially for this removed secondary memory 6. Thus, the random secondary password input here cannot match with the secondary
20 password stored in the nonvolatile memory 5 and the secondary memory 6 except for an accidental case. The state of the system hence goes on to the startup-process interrupting step 210, where the input of random passwords result in interrupting the starting process of the entire information processing system or the main unit of the information processor. Accordingly, this contrivance protects the information kept in
25 the removed secondary memory from unfair use.

Further, when the main unit of the information processor and the secondary memory 6 are removed together, and connected to another display device different from the original one, the information stored in the secondary memory 6 becomes readable

09842187-080101

only through this another display so long as no input device is connected. However, the illegitimate operator cannot tamper with the information itself stored in the secondary memory 6, and also he/she cannot use it unfairly for any other purposes and means. Since this fact has been made clear in the foregoing explanation, further
5 details will be skipped here.

As has been described in details as above, the information processing system of the present invention avoids the inconvenience of inputting the password every time the operator uses it, since the information processor starts automatically, so as to thereby
10 display automatically the information stored in the secondary memory 6 in the display device 4, when the input device 3 is not connected to the information processor. In addition, the present invention can minimize the risk of information leakage if the information processor, the secondary memory, and the like are stolen. In other words, if there is a password set with it, and if it is not connected with an input device capable
15 of inputting a password, it starts the information storage device irrespective of presence or absence of the password, and provides the display device with the information of the secondary memory, thereby improving convenience of the operator. Moreover, if there is no password set during a startup or for the secondary memory, this contrivance can offer better security for the information stored in the secondary memory by not
20 starting the device, or by not unlocking the password protection for the secondary memory. Furthermore, if there is a password set with it, this contrivance of the present invention starts the information storage device and provides the display device with the information of the secondary memory, only when the password is correctly input with a different input device, so as to reduce possibility of the information
25 leakage.